



LED LITE™

Energy Saving LED

DT641-6 Rubber Festoon Harnesses



Features:

- Rubber festoon cable must be used for all permanent outdoor installations in accordance with BS EN 60598-1:2000.
- Suitable for permanent outdoor use.
- Outdoor installations in a sheltered area in accordance with BS EN 60598-1:2000.
- Mains voltage double insulated rubber festoon harness
- Complete with 16A-6h/230V 2P+E IP44 rated plug
- IP Rating: IP44 (with GLS or golf ball lamps fitted)
- BC Lampholders
- Maximum lamp rating: up to 10W LED lamps (lamps not included)
- The high temperatures rating of the lampholder rubber seal ensures a long life seal directly onto the golf ball or GLS lamps
- Tough H05RNH-F cable (2*1.5 mm²) for permanent outdoor installations
- Power cable: round rubber cable H05RN-F cable (2*1.0 mm²)
- 3 metres lead-in to the first lampholder
- Complies with BS EN 60598-1, BS EN 60598-2:20, BS EN 61184

Specifications:

Model	Length	Distance to 1st lamp holder	Spacing between holders	Number of lamp holders
DT 641	7.5m	2.5m	50cm	10
DT 642	9m	3m	29cm	20
DT 643	15m	3m	29cm	40
DT 644	50m	3m	33cm	140
DT 645	100m	3m	100cm	100
DT 646	100m	3m	50cm	200

