



Flexible Tubing

Black Flexible Conduit

Made to CEI Standards CEI EN 50086 1-94 and CEI EN 50086 2.3-1996 degree of protection achieved with fitting is IP65.

Features and Benefits

- Plasticised PVC with shockproof rigid PVC spiral core
- Colour Black (other colours available to special order)
- Dielectric strength: greater than 2000V. 50 Hz for 15 min
- Minimum temperature 5°C
- Maximum temperature 60°C
- Bend radius: As conduit outside diameter
- Incandescent wire test at 850°C positive result – IMQ report No 1493
- Self-extinguishing to UL 94 VO Standards
- Supplied in 30m coils



Flexible Conduit.

TYPE	Int. Dia mm	Ext. Dia mm	Pack Cont.
GUAN10	10	14.7	30m
GUAN12	12	16.4	30m
GUAN16	16	20.7	30m
GUAN20	20	24.7	30m
GUAN25	25	30.6	30m
GUAN28	28	33.5	30m
GUAN32	32	38.0	30m
GUAN35	35	41.0	30m
GUAN40	40	46.4	30m
GUAN50	50	57.2	30m

Flexible Tubing

Black Flexible Conduit Handipacks

10 metres of black conduit and 10 straight fittings supplied in a handy pack.

Contents: 801 10 x GUAN16 & 10 x RAMN16
802 10 x GUAN22 & 10 x RAMN22
803 10 x GUAN20 & 10 x RAMN20



Flexible Conduit in a Handipack.

TYPE	Int. Dia mm	Ext. Dia mm	Pack Cont.
801HANDIPAK	16	20.7	1
802HANDIPAK	22	27.7	1
803HANDIPAK	20	24.7	1