

Floor Boxes

Easy to fit - Easy to handle


UNIFFB3L-90, Access Floor Box; 3 Compartment Cavity Floor Box



Specifications

- Floor box manufactured from galvanised steel
- 25 & 20mm knockouts to accept flexible conduit
- Frame and lid moulded from high impact polycarbonate
- Galvanised lid insert for strength
- Easy grip recessed lifting handle
- Compact design: 305x220mm floor cut-out
- Clamp fixing for fast installation
- Large range of accessory plates
- Special plates available to order
- Clean earthed sockets available


Top Clearance Height



Accessory Plates




FOBP300
Blank Plate




FOBP307
RJ45/LJ6C Plate




FOBP303
Standard Twin
Accessory Plate




FOBP309
Alpha Snap Plate




FOBP305
Twin Switched Sockets



FOBP310
Double LJU3/4/5 Plate



FOBP306
6x RJ45/LJ6C Data Plate



FOBP312
2 Euro Standard
50x50mm Plate

Dimensions

- Floor Cut Out: 305x220mm
- Floor Box Depth: 90mm
- Plug Top Clearance: 40mm
- Overall Frame & Lid: 315x231mm
- Frame Lid Recess: 6.5mm
- Accessories Plates: 185x89mm

UNIVOLT (UK) LTD
 Unit 4, Quadrant Park
 Black Fan Road
 Welwyn Garden City AL7 1FS
 England

Tel.: 01707 379 820

Fax: 01707 379 821

sales@univolt.co.uk

www.univolt.co.uk