

NTDR1C16

16A Single Channel DIN Rail Digital Timer (Single Module)

Features & Benefits

- DIN Rail installation
- Easy ON/OFF programme setting
- 24 Hour / 7 Day programming with 5 + 2 day option
- Digital 24 hour display
- Self cancelling manual override
- 2.5mm² Terminal connections



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	DIN Rail Mount
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Setting Type	Digital
Battery Type	NiMH 1.2V 40mAH
Power Reserve	Up to 1000 Hours
Battery Charge Time	24 hours
Contact Type	Normally Open
Program Modes	24 Hour/7 Day, Manual Override
Switch type	Single Pole, Single Throw (SPST)
Standby Consumption	<1W

Data sheet

NTDR1C16

Time / Timeguard DIN Rail Timeswitches

Number of Channels	1
Switch rating	16A Resistive, 2A Inductive, 400W LED
Shortest Switching Time	1 Minute
Programmable Slots	6 ON, 6 OFF
Permanent ON Facility	Yes
Cable Capacity (mm2)	2.5mm ²

General

Weight (g)	72
Height (mm)	90
Width (mm)	18
Depth (mm)	60
Body Construction	Polycarbonate
Product Colour	Grey
EAN Number	5012483015902
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536508090



Line Diagrams

